

Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Pavilion Stone

- Standard Colors:** Newport Grey, Pine Creek. Custom colors may be available for an upcharge.
- Grout Joint Width:** Drystacked or 3/8" Grout Joint
- Grouting Options:** Deep Raked, Drystacked, Shallow Brushed, Full Brushed or Full Smooth Tooled
- Grout Joint Color:** Natural Grey, Dark Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

- Pattern:** Stone should be installed in a horizontal ashlar pattern. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See catalog photos for recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Vertical Joints:** Avoid exceeding 2 medium stones in height.
- Horizontal Joints:** Avoid exceeding 6' to 8' in length.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed.
- Drystacked:** A polymer-modified mortar should be used for all drystacked applications.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone sizes range from 4" to 12" in height and 4" to 20" in length. Corner returns range from 2" to 10½" (nominal).
- Thickness:** ½" to 1" (nominal).
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in big boxes (140 sq ft Flats & 100 lft Corners) or Dura-Paks (14 sq ft Flats & 13 lft Corners).
- When purchasing Pavilion Stone, coverage is based on installation with tightly-fitted joints.**
(Note: Square Footage and Linear Footage quantities may vary per region)

Drystacked



PAVILION STONE

COLOR: NEWPORT GREY

Drystacked



PAVILION STONE

COLOR: PINE CREEK