BARN WOODSTONE



Installation Specifications

CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Barn WoodStone

Standard Colors: Cannery Blend, Old Frontier, Rustic Farmhouse. Custom colors may be available for an upcharge.

Grout Joint Width: Drystacked
Grouting Options: Drystacked

Grout Joint Color: Complementary mortar color is recommended

Accessories: (See Accessories section of binder)

Special Installation Notes

Pattern: Blend the pieces on the wall from several different boxes to ensure proper color.

Due to the large profile of Barn WoodStone, Coronado recommends selecting an installer that has previous

experience with precast or large tile installations.

Chalk Lines: Should be used by installer to ensure a straight and level pattern.

Sealing: Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we

suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.

Freeze-Thaw: Due to the size of this profile, extra care should be taken to ensure a full coverage of mortar on the back of each

piece, which will prevent water pooling behind the stone after it has been installed.

Installation Info: Download Coronado's latest installation instructions at www.coronado.com for information on mortar and

installation recommendations.

Profile Properties

Size: Profile sizes are 4", 6" and 8" in height and 36" in length (nominal).

Thickness: 1" (nominal).

Weight: 7 to 10 lbs. per square foot. **Packaging:** Product sold by the piece.

Drystacked



BARN WOODSTONE

COLOR: CANNERY BLEND

Drystacked



BARN WOODSTONE

COLOR: OLD FRONTIER