

6" SPLIT LIMESTONE



Installation Specifications

At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to 6" Split Limestone

- Standard Colors:** Cream, Genoa Sands, Summit Grey, or Any Custom Color
- Grout Joint Width:** Drystack
- Grouting Options:** Drystack
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

- Pattern:** Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See catalog photos for recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it's been installed.
- Drystack:** A polymer modified mortar should be used for all drystack applications.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Stone sizes 6" in height and up to 30" in length (nominal).
- Thickness:** 1" (nominal)
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in big boxes or Dura-Paks. **When purchasing 6" Split Limestone, coverage is based on installation with tightly-fitted joints.**

Drystack



6" SPLIT LIMESTONE

COLOR: CREAM