

Installation Specifications

At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to RoughCut WoodStone

- Standard Colors:** Antique White, Cedar, Deadwood, Rustic Cedar or Any Custom Color
- Grout Joint Width:** Drystack
- Grouting Options:** Drystack
- Grout Joint Color:** Complementary mortar color is recommended
- Accessories:** (See Accessories section of binder)

Special Installation Notes

- Pattern:** Blend the pieces on the wall from several different boxes to ensure proper color.
Due to the large profile of RoughCut WoodStone, Coronado recommends selecting an installer that has previous experience with precast or large tile installations.
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** Due to the size of this profile, extra care should be taken to ensure a full coverage of mortar on the back of each piece, which will prevent water pooling behind the stone after it's been installed.
- Installation Info:** Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

- Size:** Profile sizes is 6" in height and 36" in length (nominal).
- Thickness:** 1" (nominal)
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Product sold by the piece.

Drystack



ROUGH CUT WOODSTONE COLOR: DEADWOOD

Drystack



ROUGH CUT WOODSTONE COLOR: RUSTIC CEDAR