

## Installation Specifications

At [www.CORONADO.com](http://www.CORONADO.com) product specifications can be downloaded in CSI format.

### Choices Specific to Weathered Edge

- Standard Colors:** Aspen, Chablis, Coal Canyon, Crossroads Blend, Foxhill Blend, Sunhill Blend, Wisconsin Blend or Any Custom Color
- Grout Joint Width:** ½" Grout Joint or Drystack
- Grouting Options:** Deep Raked, Drystack, Full Brushed or Full Tooled
- Grout Joint Color:** Natural Grey, Natural Off-White or Complementary Color
- Accessories:** Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

### Special Installation Notes

- Pattern:** Install stone in an ashlar pattern. Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and size variation. **See catalog photos for recommended installation pattern.**
- Chalk Lines:** Should be used by installer to ensure a straight and level pattern.
- Vertical Joints:** Should be no higher than 4" to 6" on average or one large stone.
- Horizontal Joints:** Should not exceed 6' to 8'.
- Sealing:** Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.
- Freeze-Thaw:** When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it's been installed.
- Drystack:** A polymer modified mortar should be used for all drystack applications.
- Installation Info:** Download Coronado's latest installation instructions at [www.coronado.com](http://www.coronado.com) for information on mortar and installation recommendations.

### Profile Properties

- Size:** 1" to 7" in height and up to 32" in length (nominal). (If larger profile is desired, refer to Desert Ridge specification sheet).
- Thickness:** 1" to 2½"
- Weight:** 7 to 10 lbs. per square foot.
- Packaging:** Available in big boxes (100 sq ft Flats & 100 lft Corners) or Dura-Paks (12.5 sq ft Flats & 12.5 lft Corners).  
**When purchasing Weathered Edge, coverage is based on installation with tightly-fitted joints.**

Drystack



WEATHERED EDGE      COLOR: *WISCONSIN BLEND*

Drystack



WEATHERED EDGE      COLOR: *ASPEN*