

Installation Specifications

At www.CORONADO.com product specifications can be downloaded in CSI format.

Choices Specific to Industrial Ledge

Standard Colors: Shale Grey, or Any Custom Color

Grout Joint Width: Drystacked

Grouting Options: Drystacked

Grout Joint Color: Natural Grey, Natural Off-White or Complementary Color

Accessories: Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder)

Special Installation Notes

Pattern: Blend the stone on the wall from several different boxes to ensure proper color and size variation.

Chalk Lines: Should be used by installer to ensure a straight and level pattern.

Vertical Joints: Avoid exceeding 2 medium or 3 small stones in height.

Horizontal Joints: Avoid exceeding 6' to 8' in length.

Sealing: Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles.

Freeze-Thaw: When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it's been installed.

Drystacked: A polymer modified mortar should be used for all drystacked applications.

Installation Info: Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations.

Profile Properties

Size: Stone sizes are from 2", 3", 4", 5" and 7" in height and range from 4" to 30" in length (nominal).

Thickness: $\frac{3}{4}$ " to 2" (nominal)

Weight: 7 to 10 lbs. per square foot.

Packaging: Available in big boxes or Dura-Paks. **When purchasing Industrial Ledge, coverage is based on installation with tightly-fitted joints.**

The 30" long stones (1 ½" or 2" thick) stones can be tightly joined to create the illusion of a 60" piece.

Drystacked

