IDAHO DRYSTACK



Installation Specifications CSI – 3 Part Spec available at www.CORONADO.com/ArchitecturalResources

Choices Specific to Idaho Drystack

| Standard Colors: | Cape Cod Grey, Carmel Mountain, Grey Quartzite, Antique Buff, Smokey Grey, Aspen. Custom colors may be |
|----------------------------|--|
| | available for an upcharge. |
| Grout Joint Width: | 1/2" Grout Joint or Drystacked |
| Grouting Options: | Deep Raked, Drystacked, Full Brushed or Full Tooled |
| Grout Joint Color: | Natural Grey, Natural Off-White or Complementary Color |
| Accessories: | Corners, Complementary Tiles, Wall Caps, Post Caps and more. (See Accessories section of binder) |
| Special Installation Notes | |

| Pattern: | Do not install stones vertically. Blend the stone on the wall from several different boxes to ensure proper color and | |
|--------------------|---|--|
| | size variation. See catalog photos for recommended installation pattern. | |
| Chalk Lines: | Should be used by installer to ensure a straight and level pattern. | |
| Vertical Joints: | Should be no higher than 4" to 6" on average. | |
| Horizontal Joints: | Should not exceed 6' to 8'. | |
| Sealing: | Not required. However, if installed on an exterior exposed to excessive water from runoff or improper drainage, we suggest the product be sealed in that particular area to protect it from staining or spalling during freeze-thaw cycles. | |
| Freeze-Thaw: | When installing stone in a freeze-thaw environment, extra care should be taken to ensure a full coverage of mortar on the back of each stone, which will prevent water pooling behind the stone after it has been installed. | |
| Drystacked: | A polymer-modified mortar should be used for all drystacked applications. | |
| Installation Info: | Download Coronado's latest installation instructions at www.coronado.com for information on mortar and installation recommendations. | |
| Profile Properties | | |

Size: Stone sizes range from 1" to 4" in height and from 4" to 16" in length. Corner returns range from 3" to 9¹/₂" (nominal). Thickness: 1¹/₄" to 2" (nominal). Weight: 7 to 10 lbs. per square foot. Packaging: Available in big boxes (100 sq ft Flats or 100 ln ft Corners) or Dura-Paks (12.5 sq ft Flats or 12.5 ln ft Corners). When purchasing Idaho Drystack, coverage is based on installation with tightly-fitted joints. (Note: Square Footage and Linear Footage quantities may vary per region)

Drystacked



COLOR: CARMEL MOUNTAIN **IDAHO DRYSTACK**

Drystacked



IDAHO DRYSTACK

COLOR: GREY QUARTZITE